



# PROLINE® SPECIALTY



LOWBOY MODEL

COMPACT MODEL



TABLE TOP MODEL



POINT-OF-USE MODEL



Low Lead Content

## Lowboy

- Side water connections for applications where hand-room is limited.

## Table Top

- Features a convenient flat porcelain surface at 36" height, providing extra "counter space" wherever installed. All plumbing and electrical connections are made through the back of the water heater. This heater is equipped with a PEX cross-linked polymer dip tube.

## Point-of-Use

- Designed for low-demand, such as office lavatories or buildings with remote restrooms.

## Compact

- Side-mounted plumbing and electrical connections (optional top-mounted water connections for field conversion). Designed for installation under a counter, in a crawl space or in other tight spaces.

## Approved For Manufactured Housing

- All residential electric water heaters are compliant with HUD standards for mobile homes/ manufactured housing.

## Enhanced-Flow Brass Drain Valve

## Code Compliance

- Meets UBC, CEC and HUD National Codes.
- Meets the thermal efficiency and standby loss requirements of the U.S. Department of Energy and current edition of ASHRAE/IES 90.1.
- Complies with the Federal Energy Conservation Standards effective April 16, 2015, in accordance with the Energy Policy and Conservation Act (EPCA), as amended.

## Design-Listed By Underwriters Laboratories

- Certified at 300 psi test pressure and 150 psi working pressure.
- Listed according to UL 174 standards governing storage tank-type electric water heaters.

## 6-Year Limited Tank And Parts Warranty

- For complete information, consult written warranty or go to [hotwater.com](http://hotwater.com).



Model Number	Nominal Capacity	Rated Storage Volume	First Hour Rating (Gallons)	UEF	Element Wattage		Recovery @ 90°F Rise Gallons Per Hour	Dimensions in Inches			Approx. Shipping Weight (lbs)
					Standard	Maximum		A	B	C	
<b>Compact Models</b>					120V	240V					
EJC-6	6	6	N/A	N/A	1650	3000	8	15-1/4	10-3/4	14-1/4	35
EJC-10	10	9	N/A	N/A	1650	6000	8	18-1/4	12-1/4	16	41
EJCS-20	19	17	N/A	N/A	2500	6000	11	24-3/4	18-5/8	18	68
EJCT-20	19.9	18	N/A	N/A	2500	6000	11	31-5/8	25-3/4	16	68
<b>Lowboy Side-Connect Model</b>					240V						
ENJB-30*	28	26	47	0.90	4500	6000	21	30	21-3/4	22	101
ENJ-30	28	26	43	0.91	4500	6000	21	31-1/4	21-3/4	24	115
ENJB-40*	38	35	57	0.94	4500	6000	21	31-3/4	24	24	118
ENJ-40	38	35	54	0.93	4500	6000	21	33-1/2	24	26	118
<b>Table Top Model</b>					240V						
ENTT-38	38	35	55	0.90	4500	5500	21	36	24	25	150
<b>Point-Of-Use-Models</b>					120V						
EJC-2	2.5	2	N/A	N/A	1500 @ 120V		7	13-3/4	11	13-3/4	20

\*Models ship with insulation blanket.