



PROLINE® STANDARD ELECTRIC



Enhanced Heating Elements

- Dual 4500 watt elements for fast recovery and reliable operation.
- Incoloy stainless steel lower element lasts longer than standard copper element.

Dynaclean™ Diffuser Dip Tube

Coregard™ Anode Rod

Blue Diamond® Glass Coating

Enhanced-Flow Brass Drain Valve

Code Compliance

- Meets UBC, CEC and HUD National Codes.
- Meets the thermal efficiency and standby loss requirements of the U.S. Department of Energy and current edition of ASHRAE/IES 90.1.
- Complies with the Federal Energy Conservation Standards effective April 16, 2015, in accordance with the Energy Policy and Conservation Act (EPCA), as amended.

Approved for Manufactured Housing

- All residential electric water heaters are compliant with HUD standards for mobile homes/ manufactured housing.

Design-Listed by Underwriters Laboratories

- Certified at 300 psi test pressure and 150 psi working pressure.
- Listed according to UL 174 standards governing storage tank-type electric water heaters.

6-Year Limited Tank and Parts Warranty

- For complete information, consult written warranty or go to hotwater.com.



Model Number	Nominal Capacity	Rated Storage Volume	First Hour Rating (Gallons)	UEF	Recovery @ 90°F Rise Gallon Per Hour	Element Wattage 240V		Dimensions in Inches			Approx. Shipping Weight (lbs)
						Standard	Maximum	Height to Top of Tank	Height to T&P	Diameter	
Tall Models											
ENT-30†	30	27	48	0.89	21	4500	6000	46-1/2	39-1/2	19	95
ENT-40†	40	36	53	0.92	21	4500	6000	61-1/4	53-1/4	18	118
ENT-50†	50	46	62	0.93	21	4500	6000	60-1/2	51-1/4	20-1/2	125
ENT-55†	55	55	72	0.93	21	4500	6000	56-1/2	48-1/2	24	145
Short Models											
ENSB-30*	30	27	50	0.90	21	4500	6000	39	30-1/2	20	95
ENS-30†	30	27	47	0.89	21	4500	6000	39-3/4	30-1/2	22	94
ENS-40†	40	37	55	0.92	21	4500	6000	49-3/4	40-3/4	20-1/2	109
ENS-50†	50	46	57	0.92	21	4500	6000	49-1/4	40-3/8	23	161
Lowboy Top Connect Models											
ENL-20	19.9	19	N/A	N/A	21	4500	6000	30	21-1/4	20	65
ENLB-30*†	28	26	46	0.89	21	4500	6000	30	21-3/4	20	90
ENL-30†	28	26	46	0.90	21	4500	6000	30	21-3/4	22	115
ENL-36†	36	33	51	0.92	21	4500	6000	32	24	24	118
ENL-40†	38	35	49	0.89	21	4500	6000	33 1/2	24	26	118
ENLB-40*†	38	35	47	0.93	21	4500	6000	32	24	23	118
ENLB-50*†	48	44	60	0.93	21	4500	6000	34	25	26-1/2	172
ENL-50†	51	48	54	0.92	21	4500	6000	36	25	26-1/2	172

* Models ship with supplied insulation blanket. | † For 10-year tank and 10-year parts warranty, change "E" to "P" in the model number (example: ENT-30 becomes PNT).
 3/4" water connections on 8" center. | ENL-20 is a single element configuration only.
 Top T&P is not available on the 10 year lowboy models.