



## THREAD & GASKET SEALANT

Ideal for sealing threaded connections, gaskets and flanged surfaces. It is designed for trouble free, high vibration applications. It sets quickly and is for use on all common metal pipe, valves and fittings, as well as PVC, CPVC and rigid Polyethylene plastic components. It will stay flexible on piping systems that are subject to vibration and on systems that must be pressurized quickly. It won't crack, crumble harden or shrink.

### Packaging Information:

Item#	Size	
12-615	24-1/4 pt. (4 fl. oz.)	containers with applicator cap
12-620	24-1/2 pt. (8 fl. oz.)	containers with applicator cap
12-625	12-1 pt. (16 fl. oz.)	containers with applicator cap
		other sizes available

### For use on:

Water, hot & cold  
Steam  
Brine  
Sugar, liquid  
Heating oil  
Hydraulic oil  
Diesel fuel oil  
Gasoline  
Natural gas  
Petroleum solvents  
Propane  
Butane  
Kerosene  
Jet fuel (JP4, 5 & 6)  
Mineral oil  
Vegetable oil  
Compresses air  
Carbon dioxide  
Freon  
Nitrogen  
Helium  
Ammonia  
Inert gases  
Dilute acids  
Dilute caustics

Good in temperatures from -100°F. to 400°F. and pressures to 12,000 psi for liquids and 3,000 psi for gases.

# UTILITY

700 MAIN STREET, WESTBURY, NY 11590 U.S.A.  
(516) 997-6300-FAX# (516) 997-6345 / [www.UtilityChemicals.com](http://www.UtilityChemicals.com)