

BFP-90LF Back Flow Preventer • Spec Sheet



FEATURES & BENEFITS

- Lead Free Brass*
- ASSE Standard 1012 & UPC / IAMPO
- 175 PSI Max.
- 250 Deg. F Max. Backflow Temperature
- Atmospheric Vent
- ISO-9002
- Size 1/2" Union Connection

DIMENSIONS

Part #	Size
BFP-90-1/2LF	1/2" FIP

MATERIAL SPECIFICATIONS

No.	Part	Material
1 / 30	Nipple	Brass C89550
2 / 28	Packing Nipple	FIBRE
3 / 29	Nipple Nut	Brass C89550
4	Bonnet	Brass C89550
5	O-Ring Bonnet	Rubber SAE No 1052#
6	Filter	Stainless Steel 304/306
7	Snap Ring	Stainless Steel 304/306
8S/D13	Seat Packing Set	Rubber SAE #1052 & ST Steel
14	Packing Bonnet	FIBRE
15	Spring Cap	Stainless Steel 304/306
16	Spring	Stainless Steel 304/306
17	Seat House	Brass C89550
18	Body	Brass C89520
19	O-Ring Seat House	Rubber SAE No #1052
20S/D27	Seat Packing Set	Rubber SAE #1052 & ST Steel
31	Bolt	Iron
32	Name Plate	Aluminum

* This product complies with 0.25% weighted average lead content on wetted surfaces in accordance with CA AB1953.

