### Submittal Data

PROJECT:	UNIT TAG:	QUANTITY:
	TYPE OF SERVICE:	
REPRESENTATIVE:	SUBMITTED BY:	DATE:
ENGINEER:	APPROVED BY:	DATE:
CONTRACTOR:	ORDER NO.:	DATE:




### ALPHA HWR 15-29 SU/T


ALPHA HWR is designed for domestic hot water recirculation systems with a dedicated return line. It features an integrated estimator for temperature estimation and scheduling via the built-in digital timer.


Note! Product picture may differ from actual product

Conditions of Service		Pump Data		Motor Data		
Liquid:	Water	Liquid temperature range:	35.6 203 °F	Mains frequency:	60 Hz	
Temperature:	140 °F	Maximum ambient temperature:	131 °F			
Specific Gravity:	0.985	Product number:	92603113			



## Submittal Data







#### Materials:

Pump housing:	
Pump housing:	
Impeller:	

Stainless steel ASTM A351-CF8 Composite








### Company name: Created by: Phone:

		Date: 19/07/2024	
Description	Value	H [ft] ALPHA HWR 15-29 SU/T	eta [%
General information:			1
Product name:	ALPHA HWR 15-29 SU/T		-
Product No:	92603113		-
EAN number:	5715116925257	9-9-	-
Price:		8	1 80
Technical:			70
Rated flow:	7.26 US GPM		
Rated head:	7.218 ft		+ 60
		_ 5-	- 50
Pump head orientation:	9H	4	40
TF class:	95		30
Approvals:	FCC,cULus,cULDWus		
Model:	В	2	+20
Materials:		1-	+ 10
Pump housing:	Stainless steel		۲°
Pump housing:	EN 1.4308	- 0 1 2 3 4 5 6 7 8 9 10 Q[USGPM]	
Pump housing:	ASTM A351-CF8	Pumped liquid = Water	
Impeller:	Composite	Liquid temperature during operation = 140 °F Density = 61.35 lb/ft³	
Impeller:	PESU 30% gf + PESU-GF20%		٦
Installation:	g G. G. 20/0		
Range of ambient temperature:	32 131 °F	_ 20_	
-			
Maximum operating pressure:	174.92 psi		
Type of connection:	NPSM(M)	15	1
Size of connection:	1 1/4 inch		
Pressure rating for connection:	PN 12	= 10	-
Port-to-port length:	5 15/16 in		
Liquid:		5	_
Pumped liquid:	Water		
Liquid temperature range:	35.6 203 °F		
Selected liquid temperature:	140 °F		-
Density:	61.35 lb/ft <sup>3</sup>		
Electrical data:			
P1 min.:	2 W	5.31	
P1 max.:	21 W	3.46 1.77	
Mains frequency:	60 Hz		
Rated voltage:	1 x 115 V		
Minimum current consumption:	0.06 A		
Maximum current consumption:	0.41 A		
Enclosure, Type:	2		
Insulation class (IEC 85):	F		
Thermal protection:	Electronic		
Others:			
Net weight:	4.5 lb		
Gross weight:	5.16 lb		
Shipping volume:	0.25 ft <sup>3</sup>		
Sales region:	Namreg		
Country of origin:	DK	L N ÷	
Custom tariff no.:	8413.70.2005	– H   ¦	
		M	






Company name: Created by: Phone:

19/07/2024

# 92603113 ALPHA HWR 15-29 SU/T 60 Hz





Company name: Created by: Phone:

Order Data:					
osition	Your pos.	Product name	Amount	Product No	Total
		ALPHA HWR 15-29 SU/T	1	92603113	
				1	