

Submittal Data

PROJECT:	UNIT TAG:	QUANTITY:
REPRESENTATIVE: _____	TYPE OF SERVICE:	DATE: _____
ENGINEER:	SUBMITTED BY:	DATE:
CONTRACTOR:	APPROVED BY:	DATE:
	ORDER NO.:	DATE:




10 SQE07-240

Submersible pumps with variable speed motor

Note! Product picture may differ from actual product

Conditions of Service	Pump Data	Motor Data
Liquid: Water Temperature: 68 °F Specific Gravity: 1.000	Liquid temperature range: 32 .. 95 °F Product number: On request	Rated voltage: 200-240 V Mains frequency: 60 Hz Enclosure class: IP68 Insulation class: F Motor protection: Y Thermal protection: INT Motor type: MSE3



Submittal Data

Materials:

Impeller: Composite

Motor: Stainless steel

Motor: DIN W.-Nr. 1.4301

Motor: AISI 304

Qty. Description

1 10 SQE07-240



Note! Product picture may differ from actual product

Product No.: On request

3" multi-stage, submersible pump designed for domestic water supply, liquid transfer in tanks, irrigation and environmental applications. The pump has "floating" impellers, each with its own tungsten carbide/ceramic bearing.

The pump features soft starting and protection against dry-running, upthrust, overvoltage, undervoltage, overload and overtemperature.

The motor is a single-phase motor of the permanent magnet rotor type ensuring optimum efficiency within a wide load range.

The motor is fitted with a replaceable end cover with socket.

Liquid:

Pumped liquid: Water
Liquid temperature range: 32 .. 95 °F
Selected liquid temperature: 68 °F
Density: 62.29 lb/ft³

Technical:

Pump speed on which pump data are based: 10700 rpm
Rated flow: 8.81 US GPM
Rated head: 288.7 ft
Approvals: cULus
Curve tolerance: ISO9906:2012 3B

Materials:

Pump: Stainless steel
EN 1.4301
AISI 304
Impeller: Composite
ZYTEL 70G30 HSLR PA6.6-GF30
Motor: Stainless steel
DIN W.-Nr. 1.4301
AISI 304

Installation:

Maximum operating pressure: 217.56 psi
Pump outlet: 1 1/4"NPT
Minimum borehole diameter: 2.99 in

Electrical data:

Motor type: MSE3
Power input - P1: 1.55 kW
Rated power - P2: 1.54 HP
Power (P2) required by pump: 2.08 HP
Mains frequency: 60 Hz



Company name:

Created by:


Phone:

Date:



19/08/2024

Qty.	Description
1	Rated voltage: Service factor: Rated current: Power factor: Rated speed: Start. method: Enclosure class (IEC 34-5): Insulation class (IEC 85): Length of cable: Motor No: 1 x 200-240 V 2.05 8.4 A 1.00 10700 rpm DOL IP68 F 4.92 ft 96160540 Others: Net weight: Gross weight: Country of origin: Custom tariff no.: 12.1 lb 13.7 lb MX 8413.70.2004

On request 10 SQE07-240 60 Hz



Description	Value
General information:	
Product name:	10 SQE07-240
Product No:	On request
EAN number:	On request
Technical:	
Pump speed on which pump data are based:	10700 rpm
Rated flow:	8.81 US GPM
Rated head:	288.7 ft
Stages:	5
Approvals:	cULus
Curve tolerance:	ISO9906:2012 3B
Pump No:	96397413
Model:	B
Valve:	Y
Materials:	
Pump:	Stainless steel
Pump:	EN 1.4301
Pump:	AISI 304
Impeller:	Composite
Impeller:	ZYTEL 70G30 HSLR PA6.6-GF30
Motor:	Stainless steel
Motor:	DIN W.-Nr. 1.4301
Motor:	AISI 304
Installation:	
Maximum operating pressure:	217.56 psi
Pump outlet:	1 1/4"NPT
Minimum borehole diameter:	2.99 in
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	32 .. 95 °F
Selected liquid temperature:	68 °F
Density:	62.29 lb/ft³
Electrical data:	
Motor type:	MSE3
Power input - P1:	1.55 kW
Rated power - P2:	1.54 HP
Power (P2) required by pump:	2.08 HP
Mains frequency:	60 Hz
Rated voltage:	1 x 200-240 V
Service factor:	2.05
Rated current:	8.4 A
Power factor:	1.00
Rated speed:	10700 rpm
Start. method:	DOL
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Built-in motor protection:	Y
Thermal protec:	INT
Length of cable:	4.92 ft
Motor No:	96160540
Controls:	
CU 300/CU 301:	Y
Others:	
Net weight:	12.1 lb
Gross weight:	13.7 lb
Sales region:	Namreg





Company name:

Created by:


Phone:

Date:

19/08/2024

Description	Value
Country of origin:	MX
Custom tariff no.:	8413.70.2004

On request 10 SQE07-240 60 Hz



Note! All units are in [in] unless others are stated.

