

## SHC Technical Specifications

**Technical Data**

Certified to ANSI/UL Std. 174  
Conforms to CAN/CSA Std. 22.2 No. 110

**ISO 9001**  
CERTIFIED



Tested and certified by WQA against  
NSF/ANSI 372 for lead free compliance

Model	SHC 2.5	SHC 4	SHC 6
Item number	233219	234046	235089
Phase - 60/50 Hz	single	single	single
Voltage	120 V	120 V	120 V
Wattage	1300 W	1300 W	1300 W
Amperage	11.3 A	11.3 A	11.3 A
Nominal water volume	2.65 gal (10 l)	4.0 gal (15 l)	6.0 gal (22.7 l)
Weight empty	15.9 lb (7.2 kg)	19.8 lb (9.0 kg)	26.5 lb (12.0 kg)
Height (includes P&T valve)	18 <sup>11/16</sup> " (475 mm)	19 <sup>3/4</sup> " (501 mm)	20 <sup>1/2</sup> " (520 mm)
Width	11" (280 mm)	12 <sup>5/8</sup> " (320 mm)	15 <sup>1/8</sup> " (385 mm)
Depth	10 <sup>5/8</sup> " (270 mm)	12 <sup>1/2</sup> " (318 mm)	15" (380 mm)
Maximum operating pressure	150 psi (10 bar)	150 psi (10 bar)	150 psi (10 bar)
Maximum adjustable temperature	140 °F (60 °C)	140 °F (60 °C)	140 °F (60 °C)
Recovery time	18 minutes	27 minutes	45 minutes
Standby energy loss @ 131 °F (55 °C)	0.37 kWh/day	0.39 kWh/day	0.43 kWh/day
Water connections	brass 1/2" NPT	brass 1/2" NPT	brass 1/2" NPT